



# GREEN GRAFFITI COAT® NO VOC ANTIGRAFFITI COATING PRODUCT INFORMATION

Polar Industries, Inc. Box 293 Fisher Branch, Manitoba Canada R0C 0Z0  
Tel: (204) 372-8482 Fax: (204) 372-8479 www.greengraffiti.coat.com

## Background

No VOC Green Graffiti Coat is a fast drying, one component natural oil based coating designed for protection of surfaces. Safe for food contact surfaces.

## No VOC Antigrffiti Coating

Color  
Milky white on application - Clear when dry  
Reducer  
Denatured alcohol- proprietary blend

## Compatible Substrates

Painted or unpainted  
Concrete  
Wood  
Metal

## Preparation

Clean surface with non-toxic degreaser  
Dry surface

## Mixing

Stir thoroughly before using or thinning  
  
Green Graffiti Coat may be tinted up to 10 % to add color  
  
Thin as need for application

## Application

One coat  
  
Apply to clean dry surface. Expose surface to natural sunlight or UV light after application  
  
Air pressure  
HVLV 8 – 10 psi at the air cap  
Conventional 40 – 50 psi at the gun  
  
Gun setup  
1.4 – 1.6 mm or equivalent

## Dry Times

UV light  
4-20 minutes to touch  
1-3 hours to hard coat  
Natural sunlight  
4-20 minutes to touch  
1-3 hours to hard coat  
3 days to full cure

## Clean Up

Clean spray guns, gun cups, storage pots etc., thoroughly with acetone or other appropriate clean up solvent after each use.  
Follow EPA guidelines for proper storage and disposal of waste paint.

## Important

Wear personal protective equipment (PPE) and proper ventilation when exposed for long period of time.  
Wash with soap/water or acetone/water after handling. Handle spray equipment with due care and in accordance with manufacturer's recommendations. Manufacturer's warranty limited to product replacement.