



TAG MASTER REMOVE™

Background

Use no VOC Tag Remove to eliminate any graffiti from surfaces protected with No VOC Green Graffiti Coat. TAG Remover uses a natural, biodegradable, soy-based solvent that is highly effective for quick removal of paint, tar, ink, soot and oily dirt.

Remove graffiti from all surfaces.

Tag Remover

Color
Clear

Compatible Substrates

Tag Remove has been specially formulated to work on surfaces coated with NO VOC Green Graffiti Coat. Will work on virtually any surface including:

Painted or unpainted
Concrete & Cement
Wood
Metal

Preparation

Brush away surface dirt if necessary with pressure wash.

Mixing

No Mixing Required

Important

Wear personal protective equipment (PPE) and proper ventilation when exposed for long period of time. Wash with soap/water or acetone/water after handling. Handle spray equipment with due care and in accordance with manufacturer's recommendations. Manufacturer's warranty limited to product replacement.

Application

For use on GREEN GRAFFITI COAT protected surfaces:

Tag Remove may be applied directly to surface coated with No VOC Green Graffiti Coat.

Apply Tag Remove using a mop, sponge, cloth, trigger sprayer or pressure washer. Wipe surface clean with dry cloth.

For use on UNCOATED surfaces:

Graffiti removal from surfaces that do not have a protective Green Graffiti Coat may need extra use of Tag Remove and scrubbing due to markings unknown. Masonry and cement surfaces may also require etching or sanding to eliminate markings that have been absorbed below the surface. Let it sit approximately 4 minutes on plastic and 8 minutes on metal surfaces.

Dry Times

Surface will dry within a few minutes.

Clean Up

Use soap and water. Follow EPA guidelines for proper storage and disposal of waste paint.

Polar Industries, Inc., Box 293, Fisher Branch, Manitoba, CANADA R0C 0Z0
www.greengraffiti.coat ♦ polarindustry@gmail.com ♦ Tel: (204) 372-8482